



AMENDMENTS TO THE CLAIMS:

Please cancel claims 1-35 without disclaimer or prejudice.

Please add new claims 36-79.

36. (New) A machine implemented method for providing translated content, comprising the steps of:

receiving a request for translated content in a second language corresponding to content in a first language;

dividing the content into one or more translatable components;

generating an identifier for each of the translatable components;

identifying a translated component corresponding to a translatable component based on an identifier for the translatable component;

generating the translated content based on one or more translated components, identified in the identifying step; and

sending the translated content as a response to the request.

37. (New) The method according to claim 36, further comprising the step of arranging the one or more translated components in the translated content in the second language so that the format of the content in the first language is preserved.



38. (New) The method according to claim 37, wherein the step of arranging includes inserting a link contained in the content in the first language in the translated content in the second language.

39. (New) The method according to claim 37, wherein the step of arranging includes modifying a link associated with the content in the first language to obtain an updated link.

40. (New) The method according to claim 39, wherein the updated link points to an updated location associated with the translated content in the second language.

41. (New) The method according to claim 39, wherein the updated link is derived by prefixing the link using a Universal Resource Locator (URL) associated with a processing facility that provides at least a part of the translated content.

42. (New) The method according to claim 38, wherein the link includes a Universal Resource Locator (URL).



43. (New) The method according to claim 36, wherein each of the translatable components is one of:

a text segment;

an image file;

an audio clip;

a video clip;

a file; and

any combination thereof in an electronic data stream.

44. (New) The method according to claim 36, wherein the step of generating an identifier includes generating an identifier for a text segment based on at least one of a hash code, a checksum, and a mathematical algorithm based on one or more text segments.

45. (New) The method according to claim 36, wherein the content in the first language is sent from a different information processing system than where the step of receiving is performed.

46. (New) The method according to claim 36, wherein the content in the first language is parsed based on at least one markup tag into the one or more translatable components.

47. (New) The method according to claim 36, wherein the content in the first language includes a file containing at least one of a JavaScript and VBScript.



48. (New) The method according to claim 36, wherein a translatable component is derived based on a directive tag contained in the content in the first language.

49. (New) The method according to claim 48, wherein the at least one directive tag is specified via a markup comment.

50. (New) The method according to claim 36, wherein:  
the first language includes one of English, French, Spanish, German, Portuguese, Italian, Chinese, Korean, and Arabic;  
the second language includes one of English, French, Spanish, German, Portuguese, Italian, Japanese, Chinese, Korean, and Arabic; and  
the second language is different from the first language.

51. (New) The method according to claim 36, wherein the request is one of a Hyper Text Transfer Protocol (HTTP) request and a Simple Mail Transfer Protocol (SMTP) request.

52. (New) The method according to claim 36, wherein a translated component is generated by translating a corresponding translatable component in the first language with assistance of a human.

53. (New) The method according to claim 36, further comprising the step of receiving a text string from a user viewing the translated content.



54. (New) The method according to claim 53, further comprising the step of translating the text string, if the text string is in a language differing from the first language, to produce a translated text string in the first language.

55. (New) The method according to claim 54, wherein the step of translating is performed so that the translated text string is compatible with a given function utilized to provide the content in the first language.

56. (New) The method according to claim 55, wherein the step of translating the text string is by at least one of human translation and machine translation.

57. (New) The method according to claim 55, wherein the given function is a search function.

58. (New) The method according to claim 36, further comprising the steps of:  
identifying, among the one or more translatable components, at least two associated translatable components; and  
generating one or more translated components in the second language that are locked-together corresponding to the at least two associated translatable components in the first language.

59. (New) The method according to claim 36, wherein the steps of dividing the content and generating an identifier are conditioned.



60. (New) The method according to claim 59, wherein the steps of dividing the content and generating an identifier are conditioned by the following steps of:

determining a percentage of the content in the first language for which translated components are available by the step of identifying; and

conditioning the steps of dividing the content and generating an identifier based on the percentage determined.

61. (New) The method according to claim 59, wherein the condition is evaluated based on a first hash code and a second hash code, the step of evaluating further comprising the steps of:

storing a first hash code for the content in the first language;

storing the translated content;

determining a second hash code for the content in the first language;

comparing the first hash code with the second hash code;

retrieving the translated content when the first hash code matches with the second hash code; and

performing the steps of dividing the content and generating an identifier when the second hash code does not match the first hash code.

62. (New) The method according to claim 36, wherein the one or more translatable components include a text segment enclosed in an attribute of an HTML tag.



63. (New) A system for providing translated content, comprising:  
a receiver for receiving a request for translated content in a second language  
corresponding to content in a first language;  
an information processing portion configured for:  
    (a) dividing the content into one or more translatable components,  
    (b) generating an identifier for each of the translatable components,  
    (c) identifying a translated component corresponding to a translatable component  
    based on an identifier for the translatable component, and  
    (d) generating the translated content based on one or more translated components,  
    identified in (c); and  
a sending unit configured for sending the translated content as a response to the request.

64. (New) The system according to claim 63, wherein each of the translatable  
components is one of:  
a text segment;  
an image file;  
an audio clip;  
a video clip;  
a file; and  
any combination thereof in an electronic data stream.



65. (New) The system according to claim 64, wherein the step (b) of generating an identifier includes generating an identifier for a text segment based on at least one of a hash code, a checksum, and a mathematical algorithm based on one or more text segments.

66. (New) The system according to claim 63, wherein:  
the first language includes one of English, French, Spanish, German, Portuguese, Italian, Chinese, Korean, and Arabic;  
the second language includes one of English, French, Spanish, German, Portuguese, Italian, Japanese, Chinese, Korean, and Arabic; and  
the second language is different from the first language.

67. (New) The system according to claim 63, wherein a translated component is generated by translating a corresponding translatable component in the first language with assistance of a human.

68. (New) The system according to claim 63, wherein the information processing portion is further configured for receiving a text string from a user viewing the translated content.

69. (New) The system according to claim 68, wherein the information processing portion is further configured for translating the received text string, if the text string is in a language differing from the first language, to produce a translated text string in the first language.



70. (New) The system according to claim 68, wherein the step of translating the text string is performed so that the translated text string is compatible with a given function utilized to provide the content in the first language.

71. (New) The system according to claim 70, wherein the step of translating is by at least one of human translation and machine translation.

72. (New) The system according to claim 70, wherein the given function is a search function.

73. (New) A machine implemented method for providing translated content, comprising the steps of:

receiving a request for translated content in a second language corresponding to content in a first language;

identifying one or more components in the second language having corresponding components in the first language content;

presenting the one or more components in the second language in the translated content so that the appearance of the content in the first language is preserved; and

sending the one or more components in the second language as a response to the request.



74. (New) A machine implemented method for providing translated content, comprising the steps of:

receiving a request for translated content in a second language corresponding to content in a first language;

dividing the content into one or more translatable components;

identifying a translated component corresponding to at least one translatable component, wherein the translated component is produced based on a human translation;

generating the translated content based on one or more translated components, produced in the identifying step; and

sending the translated content as a response to the request.

75. (New) A method for segmenting content, comprising the steps of:

accessing content having markup tags therein;

parsing the content based on at least one of the markup tags into one or more segments, wherein the at least one of the markup tags separates the content into segments.

76. (New) The method according to claim 75, wherein each of the markup tags is configurable selectively to separate or not to separate the content into segments.

77. (New) A method for detecting a translatable component, comprising the steps of:

accessing content having markup tags therein;

parsing the content into one or more components based on the markup tags;

determining whether each of the components corresponds to a translatable component.



78. (New) The method according to claim 77, wherein at least one of the markup tags separates the content into segments.

79. (New) The method according to claim 78, wherein each of the markup tags is configurable selectively to separate or not to separate the content into segments.